


NPN General Purpose Amplifier



SOT-23

Features

- Epoxy meets UL-94 V-0 flammability rating and halogen free
- Moisture Sensitivity Level 1
- Part no. with suffix "Q" means AEC-Q101 qualified

Applications

- Linear amplification

Mechanical Data

- **Case:** SOT-23
- **Terminals:** Tin plated leads, solderable per J-STD-002 and JESD22-B102
- **Marking:** J6

■ Maximum Ratings (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Value
Collector-Base Voltage	V_{CBO}	V		50
Collector-Emitter Voltage	V_{CEO}	V		45
Emitter-Base Voltage	V_{EBO}	V		5
Collector Current -Continuous	I_C	mA		100
Total Device Dissipation	P_D	mW		200
Thermal Resistance Junction to Ambient	R_{thJA}	K/W		417
Maximum Junction Temperature	T_j	°C		150
Storage Temperature	T_{STG}	°C		-55 to +150



S9014-LQ & S9014-HQ

■ Electrical Characteristics (Ta=25°C unless otherwise noted)

Item	Symbol	Unit	Conditions	Min	Max
Collector-base breakdown voltage	$V_{(BR)CBO}$	V	$I_C=100\mu A, I_E=0$	50	
Collector-emitter breakdown voltage	$V_{(BR)CEO}$	V	$I_C=0.1mA, I_B=0$	45	
Emitter-base breakdown voltage	$V_{(BR)EBO}$	V	$I_E=100\mu A, I_C=0$	5	
Collector cut-off current	I_{CBO}	nA	$V_{CB}=50V, I_E=0$		100
Collector cut-off current	I_{CEO}	nA	$V_{CE}=35V, I_B=0$		100
Emitter cut-off current	I_{EBO}	nA	$V_{EB}=3V, I_C=0$		100
DC current gain	$h_{FE(1)}$		$V_{CE}=5.0V, I_C=1mA$	200	1000
Collector-emitter saturation voltage	$V_{CE(sat)}$	V	$I_C=100mA, I_B=5mA$		0.3
Base-emitter saturation voltage	$V_{BE(sat)}$	V	$I_C=100mA, I_B=5mA$		1
Transition frequency	f_T	MHZ	$V_{CE}=5Vdc, I_C=10mA, f=30MHz$	150	

■ Classification Of h_{FE} (1)

Rank	L	H
Range	200-450	450-1000

■ Ordering Information (Example)

PREFERRED P/N	PACKING CODE	UNIT WEIGHT(g)	MINIMUM PACKAGE(pcs)	INNER BOX QUANTITY(pcs)	OUTER CARTON QUANTITY(pcs)	DELIVERY MODE
S9014-LQ & S9014-HQ	F2	Approximate 0.01	3000	30000	120000	7" reel



S9014-LQ & S9014-HQ

■ Characteristics (Typical)

Figure 1. Static Characteristic




Figure 2. $h_{FE} - I_C$




Figure 3. $V_{BEsat} - I_C$






Figure 4. $V_{CEsat} - I_C$






S9014-LQ & S9014-HQ

■SOT-23 Package Outline Dimensions



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.035	0.045	0.90	1.15	
A1	0.000	0.004	0.00	0.10	
A2	0.035	0.041	0.90	1.05	
b	0.012	0.020	0.30	0.50	
c	0.004	0.008	0.10	0.20	
D	0.110	0.118	2.80	3.00	
E	0.047	0.055	1.20	1.40	
E1	0.089	0.100	2.25	2.55	
e	0.370TYP		0.95TYP		
e1	0.071	0.079	1.80	2.00	
L	0.220REF		0.55REF		
L1	0.012	0.020	0.30	0.50	
theta	0°	8°	0°	8°	

■SOT-23 Suggested Pad Layout



Unit: $\frac{\text{inch}}{\text{mm}}$



S9014-LQ & S9014-HQ

Disclaimer

The information presented in this document is for reference only. Yangzhou Yangjie Electronic Technology Co., Ltd. reserves the right to make changes without notice for the specification of the products displayed herein to improve reliability, function or design or otherwise.

The product listed herein is designed to be used with automotive electronics, are not designed for use in medical, life-saving, lifesustaining, or military, Yangjie or anyone on its behalf, assumes no responsibility or liability for any damages resulting from such improper use of sale.

This publication supersedes & replaces all information previously supplied. For additional information, please visit our website [http:// www.21yangjie.com](http://www.21yangjie.com) , or consult your nearest Yangjie's sales office for further assistance.